

**SILCOFLEX 595 Colorato****Safety Data Sheet**

According to Annex II to REACH - Regulation 2015/830

**SECTION 1. Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

Code: CS0019-(06260 e seg.)  
Product name: SILCOFLEX 595 Colorato (Colored)

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

Intended use: Neutral oxime silicone sealant.

**1.3. Details of the supplier of the safety data sheet**

Name: PIGAL S.R.L. A SOCIO UNICO  
Full address: Via G. Rossa, 2  
District and Country: 40053 VALSAMOGGIA - Crespellano (BO)  
ITALIA  
Tel. +39 051969068  
Fax +39 051969353

e-mail address of the competent person

responsible for the Safety Data Sheet: health.safety@pigal.it; pigalab@pigal.it

**1.4. Emergency telephone number**

For urgent inquiries refer to: 118 (contattare il centro antiveleni più vicino)/please contact your near local poison control center  
+39 051969068 ore ufficio/office hours (8.30-13; 14-17.30)

**SECTION 2. Hazards identification****2.1. Classification of the substance or mixture**

The product is not classified as hazardous pursuant to the provisions set forth in EC Regulation 1272/2008 (CLP). However, since the product contains hazardous substances in concentrations such as to be declared in section no. 3, it requires a safety data sheet with appropriate information, compliant to (EU) Regulation 2015/830.  
Hazard classification and indication:

**2.2. Label elements**

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms: --

Signal words: --

Hazard statements:

**SILCOFLEX 595 Colorato****EUH210**  
**EUH208**Safety data sheet available on request.  
Contains: Butan-2-one-O, O', O' '-(methylsiliilidin)trioxime, 2-BUTANONE OXIME  
May produce an allergic reaction.

Precautionary statements:

--

**2.3. Other hazards**

vPvB substances contained:

Dodecamethylcyclhexasiloxane

PBT substances contained:

Dodecamethylcyclhexasiloxane

During cross-linking it develops 2-Butanone oxime (CAS 96-29-7) by hydrolysis.

**SECTION 3. Composition/information on ingredients****3.2. Mixtures**

Contains:

Identification	x = Conc. %	Classification 1272/2008 (CLP)
<b>Hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics (&lt; 0,03% aromatics)</b>		
CAS -	$27 \leq x < 28,5$	Asp. Tox. 1 H304
EC 934-956-3		
INDEX -		
Reg. no. 01-2119827000-58		
<b>2-BUTANONE OXIME</b>		
CAS 96-29-7	released	Carc. 2 H351, Acute Tox. 4 H312, Eye Dam. 1 H318, Skin Sens. 1 H317
EC 202-496-6		
INDEX 616-014-00-0		
<b>Dodecamethylcyclhexasiloxane</b>		
CAS 540-97-6	$0,1 \leq x < 0,95$	Substance PBT
EC 208-762-8		Substance vPvB
INDEX -		

The full wording of hazard (H) phrases is given in section 16 of the sheet.

**SECTION 4. First aid measures**

**4.1. Description of first aid measures**

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. If the subject stops breathing, administer artificial respiration. Get medical advice/attention immediately.

INGESTION: Get medical advice/attention immediately. Do not induce vomiting. Do not administer anything not explicitly authorised by a doctor.

**4.2. Most important symptoms and effects, both acute and delayed**

Specific information on symptoms and effects caused by the product are unknown.

**4.3. Indication of any immediate medical attention and special treatment needed**

Information not available

**SECTION 5. Firefighting measures****5.1. Extinguishing media****SUITABLE EXTINGUISHING EQUIPMENT**

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

**UNSUITABLE EXTINGUISHING EQUIPMENT**

Extinguishing media to avoid: direct jets of water.

**5.2. Special hazards arising from the substance or mixture****HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE**

Do not breathe combustion products.

In case of fire: CO<sub>x</sub>, NO<sub>x</sub>, Formaldehyde, toxic fumes.

**5.3. Advice for firefighters****GENERAL INFORMATION**

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

**SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS**

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

**SECTION 6. Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures**

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

Ventilate abundantly. Avoid contact with eyes and skin.

Danger of slipping. Do not walk in the middle of spilled material.

**SILCOFLEX 595 Colorato****6.2. Environmental precautions**

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

**6.3. Methods and material for containment and cleaning up**

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

**6.4. Reference to other sections**

Any information on personal protection and disposal is given in sections 8 and 13.

**SECTION 7. Handling and storage****7.1. Precautions for safe handling**

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat.

**7.2. Conditions for safe storage, including any incompatibilities**

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Keep containers away from any incompatible materials, see section 10 for details.

**7.3. Specific end use(s)**

Information not available

**SECTION 8. Exposure controls/personal protection****8.1. Control parameters**

Regulatory References:

TLV-ACGIH

ACGIH 2018

**Hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics (< 0,03% aromatics)****Threshold Limit Value**

Type	Country	TWA/8h	STEL/15min
		mg/m3	ppm
TLV-ACGIH		5	nebbie/mist

**2-BUTANONE OXIME****Predicted no-effect concentration - PNEC**

Normal value in fresh water	0,256	mg/l
Normal value for water, intermittent release	0,118	mg/l
Normal value of STP microorganisms	177	mg/l

**SILCOFLEX 595 Colorato****Health - Derived no-effect level - DNEL / DMEL**

Route of exposure	Effects on consumers			Effects on workers				
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Inhalation			2,0 mg/m3	2,7 mg/m3			3,33 mg/m3	9,0 mg/m3
Skin		1,5 mg/kg bw/d		0,78 mg/kg/d		2,5 mg/kg bw/d		1,3 mg/kg/d

**Legend:**

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

**8.2. Exposure controls**

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

**HAND PROTECTION**

Protect hands with nitrile or chloroprene gloves (0.5 mm; permeation time > 480 min. - see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

**SKIN PROTECTION**

Wear category I professional long-sleeved overalls and safety footwear (see Directive 89/686/EEC and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

**EYE PROTECTION**

Wear airtight protective goggles (see standard EN 166).

**RESPIRATORY PROTECTION**

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type B filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

**ENVIRONMENTAL EXPOSURE CONTROLS**

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

**SECTION 9. Physical and chemical properties****9.1. Information on basic physical and chemical properties**

Appearance	pasty
Colour	transparent
Odour	Pungent (oxymic)

**SILCOFLEX 595 Colorato**

Odour threshold	Not determined
pH	Not applicable
Melting point / freezing point	< -40 °C
Initial boiling point	Not determined
Boiling range	Not available
Flash point	> 60 °C
Evaporation Rate	Not determined
Flammability of solids and gases	440°C
Lower inflammability limit	Not available
Upper inflammability limit	Not available
Lower explosive limit	Not available
Upper explosive limit	Not available
Vapour pressure	Not determined
Vapour density	>1 (Air = 1)
Relative density	1,22 - 1,25
Solubility	Not available
Partition coefficient: n-octanol/water	Not determined
Auto-ignition temperature	Not determined
Decomposition temperature	Not determined
Viscosity	> 20,5 mm2/s
Explosive properties	not applicable
Oxidising properties	not applicable
VOC (Directive 2010/75/EC) :	2,50 % - 30,75 g/litre

**SECTION 10. Stability and reactivity****10.1. Reactivity**

There are no particular risks of reaction with other substances in normal conditions of use.

**10.2. Chemical stability**

The product is stable in normal conditions of use and storage.

**10.3. Possibility of hazardous reactions**

No hazardous reactions are foreseeable in normal conditions of use and storage.

2-BUTANONE OXIME: thermal decomposition can have an explosive course. It reacts violently with strong oxidising agents and acids. Above the flash point (69°C), explosive mixtures can form with air.

**10.4. Conditions to avoid**

None in particular. However the usual precautions used for chemical products should be respected.

**SILCOFLEX 595 Colorato**

Calore, umidità.

**10.5. Incompatible materials**

Strong oxidizing agents; strong acids and bases.

**10.6. Hazardous decomposition products**

None under normal use and storage conditions.

**SECTION 11. Toxicological information**

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

**11.1. Information on toxicological effects**Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

ACUTE TOXICITY

LC50 (Inhalation) of the mixture:

Not classified (no significant component)

LD50 (Oral) of the mixture:

Not classified (no significant component)

LD50 (Dermal) of the mixture:

Not classified (no significant component)

Hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics (< 0,03% aromatics)

LD50 (Oral) > 5000 mg/kg Rat (OECD 401)

LD50 (Dermal) > 3160 mg/kg Rabbit (OECD 402)

LC50 (Inhalation) > 5266 mg/l/4h Rat (Aerosol ) OECD 403)

SKIN CORROSION / IRRITATION

Does not meet the classification criteria for this hazard class

**SILCOFLEX 595 Colorato**SERIOUS EYE DAMAGE / IRRITATION

Does not meet the classification criteria for this hazard class

RESPIRATORY OR SKIN SENSITISATION

May produce an allergic reaction. Contains: Butan-2-one-O, O', O' '-(methylsiliidid)trioxime  
2-BUTANONE OXIME

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class Viscosity: > 20,5 mm<sup>2</sup>/s

**SECTION 12. Ecological information**

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

**12.1. Toxicity**

Hydrocarbons, C15-C20, n-alkanes,  
isoalkanes, cyclics (< 0,03% aromatics)

LC50 - for Fish

> 1028 mg/l/96h *Scophthalmus maximus*

EC50 - for Crustacea

> 3193 mg/l/48h *Acartia tonsa*

EC50 - for Algae / Aquatic Plants

> 10000 mg/l/72h *Skeletonema costatum*

**12.2. Persistence and degradability**

Hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics (< 0,03% aromatics)  
- 74% (28d, seawater - OECD 306)



**SILCOFLEX 595 Colorato**

Rapidly degradable

**12.3. Bioaccumulative potential**

Information not available

**12.4. Mobility in soil**

Information not available

**12.5. Results of PBT and vPvB assessment**

vPvB substances contained:

Dodecamethylcyclohexasiloxane

PBT substances contained:

Dodecamethylcyclohexasiloxane

**12.6. Other adverse effects**

Information not available

**SECTION 13. Disposal considerations****13.1. Waste treatment methods**

Reuse, when possible. Neat product residues should be considered special non-hazardous waste.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

EU disposal code: 08 04 10 Waste adhesives and sealants other than those mentioned in 08 04 09.

**SECTION 14. Transport information**

The product is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RID), of the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations.

**14.1. UN number**

Not applicable

**14.2. UN proper shipping name**

Not applicable

**14.3. Transport hazard class(es)**

**SILCOFLEX 595 Colorato**

Not applicable

**14.4. Packing group**

Not applicable

**14.5. Environmental hazards**

Not applicable

**14.6. Special precautions for user**

Not applicable

**14.7. Transport in bulk according to Annex II of Marpol and the IBC Code**

Information not relevant

**SECTION 15. Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

Seveso Category - Directive 2012/18/EC: None

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

None

Substances in Candidate List (Art. 59 REACH)

Dodecamethylcyclohexasiloxane

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None

Substances subject to the Rotterdam Convention:

**SILCOFLEX 595 Colorato**

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Information not available

**15.2. Chemical safety assessment**

It is not foreseen a chemical safety assessment.

**SECTION 16. Other information**

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

<b>Carc. 2</b>	Carcinogenicity, category 2
<b>Acute Tox. 4</b>	Acute toxicity, category 4
<b>Asp. Tox. 1</b>	Aspiration hazard, category 1
<b>Eye Dam. 1</b>	Serious eye damage, category 1
<b>Eye Irrit. 2</b>	Eye irritation, category 2
<b>Skin Irrit. 2</b>	Skin irritation, category 2
<b>Skin Sens. 1</b>	Skin sensitization, category 1
<b>H351</b>	Suspected of causing cancer.
<b>H312</b>	Harmful in contact with skin.
<b>H304</b>	May be fatal if swallowed and enters airways.
<b>H318</b>	Causes serious eye damage.
<b>H319</b>	Causes serious eye irritation.
<b>H315</b>	Causes skin irritation.
<b>H317</b>	May cause an allergic skin reaction.
<b>EUH210</b>	Safety data sheet available on request.

**LEGEND:**

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%

**SILCOFLEX 595 Colorato**

- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

**GENERAL BIBLIOGRAPHY**

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
  2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
  3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
  4. Regulation (EU) 2015/830 of the European Parliament
  5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
  6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
  7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
  8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
  9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
  10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
  11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
  12. Regulation (EU) 2016/1179 (IX Atp. CLP)
  13. Regulation (EU) 2017/776 (X Atp. CLP)
- The Merck Index. - 10th Edition
  - Handling Chemical Safety
  - INRS - Fiche Toxicologique (toxicological sheet)
  - Patty - Industrial Hygiene and Toxicology
  - N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
  - IFA GESTIS website
  - ECHA website
  - Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

**Note for users:**

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.