

DECLARED PERFORMANCE

According to Annex III of Reg. (EU) n°305/2011

SILCOFLEX 599 transparent

DOP CS0012-M-01

EN 15651-1: F-EXT-INT

Silicone sealant for facades, for interior and exterior application

EN 15651-2: G

Silicone sealant used for sealing glazing application

Address of manufacturer

PIGAL S.p.A
Via G. Rossa, 2 40053 Località Crespellano
VALSAMOGGIA (BO) – ITALIA

Evaluation and verification of the construction product performance systems, according to Annex V:

System 3, System 3 for reaction to fire

The notified body **GINGER CEBTP**, identification number **0074**, performed the determination of the product-type and fire behavior under System 3, in reference to EN 15651, releasing the test report:

The performance of the product identified is in conformity with the declared performance (see below). This declaration of performance is issued under the sole responsibility of the manufacturer.

Valsamoggia, 23/06/2014

Carlo Alberto GOLDONI
Legal representative - PIGAL S.p.A.



DECLARED PERFORMANCEEN 15651-1: **F-EXT-INT Class 25 LM**EN 15651-2: **G Class 25 LM**

Conditioning: Method A (ISO 8340)

Substrate: Glass (without primer), Aluminum (without primer)

Essential characteristics	performance	Harmonized specification
Reaction to fire (EN 13501)	Class E	
Release of chemical dangerous to the environment and health	See product safety data sheet	
Water tightness and air tightness		EN 15651-1 & 2: 2012
Resistance to flow (ISO 7390)	≤ 3 mm	
Loss of volume (ISO 10563)	≤ 10 %	
Tensile properties at maintained extension after immersion in water (ISO 10590)	No failure	
Elastic recovery (ISO 7389)	≥ 70 %	
Durability	No failure	