

N.P.T. S.r.I. U-BOND 2K ULTRA part A

Revision nr.2 Dated 29/5/2015 Printed on 29/5/2015 Page n. 1 / 7

Safety data sheet

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name U-BOND 2K ULTRA part A

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use Two components, polyurethane based, adhesive.

1.3. Details of the supplier of the safety data sheet

Name N.P.T. S.r.I. Full address via Guido Rossa 2

District and Country 40053 Valsamoggia - Loc. Crespellano (BO)

Italy

Tel. +39 051 969109 Fax +39 051 969837

e-mail address of the competent person

responsible for the Safety Data Sheet infoSDS@nptsrl.com

1.4. Emergency telephone number

For urgent inquiries refer to Laboratories and manufactory plant - Gropello Cairoli (PV)

+39 0382 815132 (avaiable from Monday to Friday, only in the following office hours:

8.30-12.30, 13.30-17.00).

SECTION 2. Hazards identification.

2.1. Classification of the substance or mixture.

The product is not classified as hazardous pursuant to the provisions set forth in EC Regulation 1272/2008 (CLP). However, since the product contains hazardous substances in concentrations such as to be declared in section no. 3, it requires a safety data sheet with appropriate information, compliant to EC Regulation 1907/2006 and subsequent amendments.

2.1.1. Regulation 1272/2008 (CLP) and following amendments and adjustments.

Hazard classification and indication: --

2.2. Label elements.

Hazard pictograms: --

Signal words: --

Hazard statements: --

Precautionary statements: --

2.3. Other hazards.

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

SECTION 3. Composition/information on ingredients.

3.1. Substances.

Information not relevant.

FΝ



N.P.T. S.r.l.

U-BOND 2K ULTRA part A

Revision nr.2 Dated 29/5/2015 Printed on 29/5/2015 Page n. 2 / 7

SECTION 3. Composition/information on ingredients. .../>>

3.2. Mixtures.

Contains:

Identification. Conc. %. Classification 67/548/EEC. Classification 1272/2008 (CLP).

PROPOXYLATED ETHYLENE DIAMINE.

CAS. 51178-86-0 8.5 - 10 Xi R36

Eye Irrit. 2 H319

EC. INDFX

Note: Upper limit is not included into the range.

The full wording of the Risk (R) and hazard (H) phrases is given in section 16 of the sheet.

T+ = Very Toxic(T+), T = Toxic(T), Xn = Harmful(Xn), C = Corrosive(C), Xi = Irritant(Xi), O = Oxidizing(O), E = Explosive(E), F+ = Extremely Flammable(F+), F = Highly Flammable(F), N = Dangerous for the Environment(N)

SECTION 4. First aid measures.

4.1. Description of first aid measures.

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: Remove contaminated clothing. Wash immediately with plenty of water. If irritation persists, get medical advice/attention. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. In the event of breathing difficulties, get medical advice/attention immediately.

INGESTION: Get medical advice/attention. Induce vomiting only if indicated by the doctor. Never give anything by mouth to an unconscious person, unless authorised by a doctor.

4.2. Most important symptoms and effects, both acute and delayed.

For symptoms and effects caused by the contained substances, see chap. 11.

4.3. Indication of any immediate medical attention and special treatment needed.

Information not available.

SECTION 5. Firefighting measures.

5.1. Extinguishing media.

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

5.2. Special hazards arising from the substance or mixture.

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Do not breathe combustion products.

5.3. Advice for firefighters.

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health.

Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures.

6.1. Personal precautions, protective equipment and emergency procedures.

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions.

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up.

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.





N.P.T. S.r.I. U-BOND 2K ULTRA part A

Revision nr.2 Dated 29/5/2015 Printed on 29/5/2015 Page n. 3 / 7

SECTION 6. Accidental release measures. .../>>

Make sure the leakage site is well aired. Check incompatibility for container material in section 7. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections.

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage.

7.1. Precautions for safe handling.

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat.

7.2. Conditions for safe storage, including any incompatibilities.

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Keep containers away from any incompatible materials, see section 10 for details.

Storage class TRGS 510 (Germany): 10

7.3. Specific end use(s).

Information not available.

SECTION 8. Exposure controls/personal protection.

8.1. Control parameters.

Information not available

8.2. Exposure controls.

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear (see Directive 89/686/EEC and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type B filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529. ENVIRONMENTAL EXPOSURE CONTROLS.

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

SECTION 9. Physical and chemical properties.

9.1. Information on basic physical and chemical properties.

Appearance liquid Colour white Odour typical Not available. Odour threshold. Not available. Melting point / freezing point. Not available Initial boiling point. Not available. Boiling range. Not available. Flash point. 150 °C



U-BOND 2K ULTRA part A

Revision nr.2 Dated 29/5/2015 Printed on 29/5/2015 Page n. 4 / 7

SECTION 9. Physical and chemical properties. .../>>

Evaporation rate Not available. Flammability (solid, gas) Not available. Lower inflammability limit. Not available Upper inflammability limit. Not available. Lower explosive limit. Not available. Upper explosive limit. Not available. Vapour pressure. Not available. Not available. Vapour density Relative density. 1.35 Kg/I Not available. Solubility Partition coefficient: n-octanol/water Not available. Auto-ignition temperature. Not available. Not available. Decomposition temperature. Viscosity Not available. Not available Explosive properties Oxidising properties Not available.

9.2. Other information.

VOC (Directive 1999/13/EC): 0
VOC (volatile carbon): 0

SECTION 10. Stability and reactivity.

10.1. Reactivity.

There are no particular risks of reaction with other substances in normal conditions of use.

10.2. Chemical stability.

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions.

No hazardous reactions are foreseeable in normal conditions of use and storage.

10.4. Conditions to avoid.

None in particular. However the usual precautions used for chemical products should be respected.

10.5. Incompatible materials.

Information not available.

10.6. Hazardous decomposition products.

Information not available.

SECTION 11. Toxicological information.

11.1. Information on toxicological effects.

PROPOXYLATED ETHYLENE DIAMINE.

LD50 (Oral). > 2000 mg/kg Rattus sp. LD50 (Dermal). > 2000 mg/kg Oryctolagus sp.

SECTION 12. Ecological information.

12.1. Toxicity.

Information not available.

12.2. Persistence and degradability.

Information not available.

12.3. Bioaccumulative potential.

Information not available

12.4. Mobility in soil.

Information not available.

12.5. Results of PBT and vPvB assessment.

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

E١



N.P.T. S.r.I. U-BOND 2K ULTRA part A

Revision nr.2 Dated 29/5/2015 Printed on 29/5/2015 Page n. 5 / 7

SECTION 12. Ecological information. .../>>

12.6. Other adverse effects.

Information not available.

SECTION 13. Disposal considerations.

13.1. Waste treatment methods.

Reuse, when possible. Neat product residues should be considered special non-hazardous waste.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information.

14.1. UN number.

Not applicable.

14.2. UN proper shipping name.

Not applicable.

14.3. Transport hazard class(es).

Not applicable.

14.4. Packing group.

Not applicable.

14.5. Environmental hazards.

Not applicable.

14.6. Special precautions for user.

Not applicable.

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code.

Information not relevant.

SECTION 15. Regulatory information.

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture.

Seveso category.

None

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006.

None.

Substances in Candidate List (Art. 59 REACH).

None.

Substances subject to authorisarion (Annex XIV REACH).

None.

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None.

Healthcare controls.

Information not available.

German regulation on the classification of substances hazardous to water (VwVwS 2005).

F١



N.P.T. S.r.I. U-BOND 2K ULTRA part A

Revision nr.2 Dated 29/5/2015 Printed on 29/5/2015 Page n. 6 / 7

SECTION 15. Regulatory information. .../>>

WGK 2: Hazard to waters

15.2. Chemical safety assessment.

No chemical safety assessment has been processed for the mixture and the substances it contains.

SECTION 16. Other information.

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Eye Irrit. 2 Eye irritation, category 2
H319 Causes serious eye irritation.

EUH210 Safety data sheet available on request.

Text of risk (R) phrases mentioned in section 2-3 of the sheet:

R36 IRRITATING TO EYES.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

- 1. Directive 1999/45/EC and following amendments
- 2. Directive 67/548/EEC and following amendments and adjustments
- 3. Regulation (EU) 1907/2006 (REACH) of the European Parliament
- 4. Regulation (EU) 1272/2008 (CLP) of the European Parliament
- 5. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
- 6. Regulation (EU) 453/2010 of the European Parliament
- 7. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
- 8. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
- 9. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
- 10. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
- 11. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
- The Merck Index. 10th Edition
- Handling Chemical Safety
- Niosh Registry of Toxic Effects of Chemical Substances
- INRS Fiche Toxicologique (toxicological sheet)
- Patty Industrial Hygiene and Toxicology
- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition



N.P.T. S.r.I. U-BOND 2K ULTRA part A

Revision nr.2 Dated 29/5/2015 Printed on 29/5/2015 Page n. 7 / 7

on nr.2 29/5/2015 Lon 29/5/2015

SECTION 16. Other information. .../>>

- ECHA website

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

Changes to previous review: The following sections were modified: 02 / 11 / 12 / 13 / 15 / 16.

N.P.T. S.r.I. U-BOND 2K ULTRA part B

Revision nr.2 Dated 04/06/2015 Printed on 04/06/2015 Page n. 1 / 10

Page

Safety data sheet

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name U-BOND 2K ULTRA part B

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use Two components, polyurethane based, adhesive.

1.3. Details of the supplier of the safety data sheet

Name N.P.T. S.r.I.
Full address via Guido Rossa 2

District and Country 40053 Valsamoggia - Loc. Crespellano (BO)

Italy

Tel. +39 051 969109 Fax +39 051 969837

e-mail address of the competent person

responsible for the Safety Data Sheet infoSDS@nptsrl.com

1.4. Emergency telephone number

For urgent inquiries refer to Laboratories and manufactory plant - Gropello Cairoli (PV)

+39 0382 815132 (avaiable from Monday to Friday, only in the following office hours:

8.30-12.30, 13.30-17.00).

SECTION 2. Hazards identification.

2.1. Classification of the substance or mixture.

The product is classified as hazardous pursuant to the provisions set forth in EC Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of EC Regulation 1907/2006 and subsequent amendments.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Carcinogenicity, category 2 H351 Suspected of causing cancer.

Acute toxicity, category 4 H332 Harmful if inhaled.

Specific target organ toxicity - repeated exposure, category H373 May cause damage to organs through prolonged or repeated

exposure.

Eye irritation, category 2 H319 Causes serious eye irritation.
Skin irritation, category 2 H315 Causes skin irritation.
Specific target organ toxicity - single exposure, category 3 H335 May cause respiratory irritation.

Respiratory sensitization, category 1

H334

May cause allergy or asthma symptoms or breathing

difficulties if inhaled.

Skin sensitization, category 1 H317 May cause an allergic skin reaction.

2.2. Label elements.

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words: Danger

Hazard statements:

H351 Suspected of causing cancer.

H332 Harmful if inhaled.

H373 May cause damage to organs through prolonged or repeated exposure.

H319 Causes serious eye irritation.



U-BOND 2K ULTRA part B

Revision nr.2 Dated 04/06/2015 Printed on 04/06/2015 Page n. 2 / 10

SECTION 2. Hazards identification. .../>>

H315 Causes skin irritation.

H335 May cause respiratory irritation.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317 May cause an allergic skin reaction.

EUH204 Contains isocyanates. May produce an allergic reaction.

Precautionary statements:

P201 Obtain special instructions before use.

P280 Wear protective gloves / clothing and eye / face protection.
P284 [In case of inadequate ventilation] wear respiratory protection.

P304+P340 IF INHALED: remove person to fresh air and keep comfortable for breathing.

P308+P313 IF exposed or concerned: Get medical advice / attention.
P403+P233 Store in a well-ventilated place. Keep container tightly closed.

Contains: DIPHENYLMETHANE DIISOCYANATE, ISOMERS AND HOMOLOGUES.

DIPHENYLMETHANE-2,4'-DIISOCYANATE DIPHENYLMETHANE-4,4'-DIISOCYANATE

2.3. Other hazards.

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

SECTION 3. Composition/information on ingredients.

3.1. Substances.

Information not relevant

3.2. Mixtures.

Contains:

Identification. Conc. %. Classification 1272/2008 (CLP). DIPHENYLMETHANE DIISOCYANATE, ISOMERS AND HOMOLOGUES.

CAS. 9016-87-9 24 - 25,5 Carc. 2 H351, Acute Tox. 4 H332, STOT RE 2 H373, Eye Irrit. 2 H319, Skin Irrit. 2 H315,

STOT SE 3 H335, Resp. Sens. 1 H334, Skin Sens. 1 H317

EC.

INDEX.

DIPHENYLMETHANE-4,4'-DIISOCYANATE

CAS. 101-68-8 4,5 - 5 Carc. 2 H351, Acute Tox. 4 H332, STOT RE 2 H373, Eye Irrit. 2 H319, Skin Irrit. 2 H315,

STOT SE 3 H335, Resp. Sens. 1 H334, Skin Sens. 1 H317, Note 2 C

EC. 202-966-0 INDEX. 615-005-00-9

Reg. no. 01-2119457014-47-XXXX

DIPHENYLMETHANE-2,4'-DIISOCYANATE

CAS. 5873-54-1 2,5 - 3 Carc. 2 H351, Acute Tox. 4 H332, STOT RE 2 H373, Eye Irrit. 2 H319, Skin Irrit. 2 H315,

STOT SE 3 H335, Resp. Sens. 1 H334, Skin Sens. 1 H317, Note 2 C

EC. 227-534-9 INDEX. 615-005-00-9

Reg. no. 01-2119480143-45-XXXX

Note: Upper limit is not included into the range.

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures.

4.1. Description of first aid measures.

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention immediately. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. If the subject stops breathing, administer artificial respiration. Get medical advice/attention immediately. INGESTION: Get medical advice/attention immediately. Do not induce vomiting. Do not administer anything not explicitly authorised by a doctor.

4.2. Most important symptoms and effects, both acute and delayed.

For symptoms and effects caused by the contained substances, see chap. 11.

4.3. Indication of any immediate medical attention and special treatment needed.

Information not available.



U-BOND 2K ULTRA part B

Revision nr.2 Dated 04/06/2015 Printed on 04/06/2015 Page n. 3 / 10

SECTION 5. Firefighting measures.

5.1. Extinguishing media.

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

5.2. Special hazards arising from the substance or mixture.

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Do not breathe combustion products.

5.3. Advice for firefighters.

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures.

6.1. Personal precautions, protective equipment and emergency procedures.

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions.

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up.

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Check incompatibility for container material in section 7. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections.

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage.

7.1. Precautions for safe handling.

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat.

7.2. Conditions for safe storage, including any incompatibilities.

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Keep containers away from any incompatible materials, see section 10 for details.

SECTION 8. Exposure controls/personal protection.

8.1. Control parameters.

Regulatory References:

AUS	Österreich	Grenzwerteverordnung 2011 - GKV 2011
BEL	Belgique	AR du 11/3/2002. La liste est mise à jour pour 2010
DEU	Deutschland	MAK-und BAT-Werte-Liste 2012
ESP	España	INSHT - Límites de exposición profesional para agentes químicos en España 2015
FRA	France	JORF n°0109 du 10 mai 2012 page 8773 texte n° 102
GRC	Ελλάδα	ΕΦΗΜΕΡΙΣ ΤΗΣ ΚΥΒΕΡΝΗΣΕΩΣ -ΤΕΥΧΟΣ ΠΡΩΤΟ Αρ. Φύλλου 19 - 9 Φεβρουαρίου 2012
IRL	Éire	Code of Practice Chemical Agent Regulations 2011
ITA	Italia	Decreto Legislativo 9 Aprile 2008, n.81



U-BOND 2K ULTRA part B

Revision nr.2 Dated 04/06/2015 Printed on 04/06/2015 Page n. 4 / 10

SECTION 8. Exposure controls/personal protection. .../>>

POL Polska ROZPORZĄDZENIE MINISTRA PRACY I POLITYKI SPOŁECZNEJ z dnia 16 grudnia 2011r

SWE Sverige Occupational Exposure Limit Values, AF 2011:18

TLV-ACGIH ACGIH 2014

DIPHENYLMETHANE DIISOCYANATE, ISOMERS AND HOMOLOGUES.								
Threshold Limit Value.								
Type	Country	TWA/8h		STEL/15	min			
		mg/m3	ppm	mg/m3	ppm			
OEL	ITA		0,005					
TLV-ACGIH			0,005					

reshold Limit Valu										
Type	Country	TWA/8		STEL/15	STEL/15min					
		mg/m3	ppm	mg/m3	ppm					
MAK	AUS	0,05	0,005	0,1	0,01					
VLEP	BEL	0,052	0,005							
AGW	DEU	0,05		0,05						
MAK	DEU	0,05		0,05			INHAL.			
MAK	DEU	0,05		0,05			SKIN.			
VLA	ESP	0,052	0,005							
VLEP	FRA	0,1	0,01	0,2	0,02					
TLV	GRC	0,2		0,2						
OEL	IRL	0,02		0,07						
NDS	POL	0,05		0,2						
MAK	SWE	0,03	0,002	0,05 (C)	0,005 (C)					
TLV-ACGIH		0,051	0,005							
edicted no-effect c	oncentrat	ion - PN	EC.							
Normal value in fre	esh water						1,01	mg/l		
Normal value in ma	arine wate	r					0,11	mg/l		
Normal value of S	TP microo	ganisms	6				1,01	mg/l		
Normal value for the							1,01	mg/kg		
ealth - Derived no-e										
	Effects on consumers.						Effects on workers			
Route of exposure	Acute local Acu		Acute	Chronic	Chronic	Acute local	Acute	Chronic	Chronic	
·		:	systemic	local	systemic		systemic	local	systemi	
Inhalation.					•	0,1	0,1	0,05	0,05	
						mg/m3	mg/m3	mg/m3	mg/m3	
Skin.						VND	50			

		DIF	PHENYLMETHA	NE-2,4'-DIISO	CYANATE			
Predicted no-effect con	centration - P	NEC.						
Normal value in fresh	water			1,01	mg/l			
Normal value in mari	ne water			0,11	mg/l			
Normal value of STP	microorganisn	าร		1,01	mg/l			
Normal value for the	terrestrial com	partment		1,01	mg/kg			
Health - Derived no-effe	ect level - DNE	L / DMEL						
	Effects on c	onsumers.			Effects on workers			
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Inhalation.		•		-	0,1 mg/m3	0,1 mg/m3	0,05 mg/m3	0,05 mg/m3
Skin.					VND	50 mg/kg/d	-	-

Legend:

(C) = CEILING; INHAL = Inhalable Fraction; RESP = Respirable Fraction; THORA = Thoracic Fraction. VND = hazard identified but no DNEL/PNEC available; NEA = no exposure expected; NPI = no hazard identified.

8.2. Exposure controls.

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.





U-BOND 2K ULTRA part B

Revision nr.2 Dated 04/06/2015 Printed on 04/06/2015 Page n. 5 / 10

SECTION 8. Exposure controls/personal protection. .../>>

Exposure levels must be kept as low as possible to avoid significant build-up in the organism. Manage personal protective equipment so as to guarantee maximum protection (e.g. reduction in replacement times).

HAND PROTECTION

Protect your hands with work gloves, category III (ref. standard EN 374). For the final choice of material you need to assess the type of use. In case of contact for the short term or as protection against splashes, use gloves made of butyl rubber or nitrile (0.4mm thickness, permeation time <30 min.). In the event of continued exposure use Viton gloves (0.4mm thickness, permeation time> 30 min.). Contaminated gloves should be removed.

SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Directive 89/686/EEC and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

RESPIRATORY PROTECTION

In case of exceeding the threshold value (eg, TLV-TWA) of the substance or one or more of the substances present in the product, it is advisable to wear a mask with filter type A for organic vapors, the class (1, 2 or 3) must be chosen according to the limit concentration of use (1000, 5000 or 10000 ppm) (ref. standard EN 14387).

ENVIRONMENTAL EXPOSURE CONTROLS.

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

SECTION 9. Physical and chemical properties.

9.1. Information on basic physical and chemical properties.

Appearance liquid Colour black typical Odour Not available. Odour threshold. рH. Not available. Melting point / freezing point. Not available. Initial boiling point. Not available. Boiling range. Not available. Flash point. 200 °C Not available. Evaporation rate Flammability (solid, gas) Not available. Lower inflammability limit. Not available. Upper inflammability limit. Not available. Lower explosive limit. Not available Upper explosive limit. Not available. Vapour pressure. 0.01 Pa Vapour density Not available. Relative density. 1,7 Kq/I Solubility Not available Partition coefficient: n-octanol/water Not available. Not available Auto-ignition temperature. Decomposition temperature. Not available. Viscosity Not available. Not available Explosive properties Oxidising properties Not available.

9.2. Other information.

VOC (Directive 1999/13/EC): 0
VOC (volatile carbon): 0

SECTION 10. Stability and reactivity.

10.1. Reactivity.

There are no particular risks of reaction with other substances in normal conditions of use.

10.2. Chemical stability.

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions.

No hazardous reactions are foreseeable in normal conditions of use and storage.

10.4. Conditions to avoid.

None in particular. However the usual precautions used for chemical products should be respected.

10.5. Incompatible materials.

Information not available.





N.P.T. S.r.I. U-BOND 2K ULTRA part B

Revision nr.2 Dated 04/06/2015 Printed on 04/06/2015 Page n. 6 / 10

SECTION 10. Stability and reactivity. .../>>

10.6. Hazardous decomposition products.

Information not available.

SECTION 11. Toxicological information.

11.1. Information on toxicological effects.

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

This product must be handled carefully because of its possible carcinogenic effects. Anyway, currently available data do not allow us to comprehensively assess this product.

Acute effects: inhalation of this product is harmful.

Exposure symptoms may include: stinging and irritated eyes, mouth, nose, throat; cough, respiratory disorders, dizziness, headache, nausea and sickness. In the most serious cases, inhalation of this product may cause larynx and bronchial tube edema and irritation, chemical pneumonia and pulmonary edema.

This product may cause functional disorders or morphological mutations after repeated or prolonged exposure and/or may accumulate inside the human body and is thus graded as dangerous.

Acute effects: stinging eyes. Symptoms may include: rubescence, edema, pain and lachrymation.

Ingestion may cause health problems, including stomach pain and sting, nausea and sickness.

Acute effects: contact with skin may cause: irritation, erythema, edema, dryness and chapped skin.

Ingestion may cause health disorders, including stomach pain and sting, nausea and sickness.

Acute effects: inhalation of this product may irritate the lower and upper respiratory tract and cause cough and respiratory disorders; at higher concentrations it can also cause pulmonary edema. Ingestion may cause health problems, including stomach pain and sting, nausea and sickness.

Inhalation of this product causes sensitization, which may then give rise to a series of inflammatory episodes, most of all characterized by obstruction and affecting the respiratory system. Sometimes, sensitization phenomena arise together with evident rhinitis and asthma.

Damages to the respiratory system depend on the inhaled quantity, on the product concentration in the working environment and on the exposure time.

Upon contact with skin, this product causes sensitization (dermatitis). Dermatitis derives from skin irritation on the areas which repeatedly come into contact with the sensitizing agent. Cutaneous lesions may include: erythemas, edemas, papules, vesicles, pustules, scurvies, ulcerations and exudative phenomena, whose intensity varies according to illness seriousness and affected areas. Erythemas, edemas and exudative phenomena prevail during the acute phase. Scurfy skin, dryness, ulcerations and skin thickening prevail during the chronic phase. This product contains isocyanates.

Producer's specifications are as follows:

Ready-to-use products containing isocyanates may irritate mucosas, particularly those of the respiratory system, and may give rise to hypersensitivity reactions. Vapour or aerosol inhalation may lead to sensitization.

Please take all the measures used for all solvent-containing products while manipulating isocyanate-containing products. Avoid vapour and aerosol inhalation.

People with allergic or asthmatic precedents or subject to respiratory disorders should not handle products containing isocyanates.

DIPHENYLMETHANE DIISOCYANATE, ISOMERS AND HOMOLOGUES.

LD50 (Oral). > 10000 mg/kg Rattus sp. LD50 (Dermal). > 9400 mg/kg Oryctolagus sp. LC50 (Inhalation). 0,31 mg/l/4h Rattus sp.

DIPHENYLMETHANE-2,4'-DIISOCYANATE

LD50 (Oral). > 2000 mg/kg Rattus sp. LD50 (Dermal). > 9400 mg/kg Oryctolagus sp.

LC50 (Inhalation). 1,5 mg/l Rattus sp.

DIPHENYLMETHANE-4,4'-DIISOCYANATE

LD50 (Oral). > 2000 mg/kg Rattus sp. LD50 (Dermal). > 9400 mg/kg Oryctolagus sp. LC50 (Inhalation). 2,24 mg/l Rattus sp.

SECTION 12. Ecological information.

12.1. Toxicity.

DIPHENYLMETHANE DIISOCYANATE, ISOMERS AND HOMOLOGUES.

LC50 - for Fish. > 1000 mg/l/96h Danio rerio

EC50 - for Algae / Aquatic Plants. > 1640 mg/l/72h Scenedesmus subspicatus

Chronic NOEC for Crustacea. > 10 mg/l Daphnia magna





N.P.T. S.r.I. **U-BOND 2K ULTRA part B**

Revision nr.2 Dated 04/06/2015 Printed on 04/06/2015 Page n. 7 / 10

SECTION 12. Ecological information. .../>>

DIPHENYLMETHANE-2,4'-DIISOCYANATE

LC50 - for Fish.

> 1000 mg/l/96h Danio rerio > 1640 mg/l/72h Scenedesmus subspicatus EC50 - for Algae / Aquatic Plants.

Chronic NOEC for Crustacea.

> 10 mg/l Daphnia magna

DIPHENYLMETHANE-4.4'-DIISOCYANATE

LC50 - for Fish.

> 1000 mg/l/96h Danio rerio

Chronic NOEC for Algae / Aquatic Plants.

1640 mg/l Desmodesmus subspicatus

12.2. Persistence and degradability.

DIPHENYLMETHANE DIISOCYANATE, ISOMERS AND HOMOLOGUES. NOT rapidly biodegradable.

12.3. Bioaccumulative potential.

DIPHENYLMETHANE-2,4'-DIISOCYANATE

BCF

200 Cyprinus carpio

12.4. Mobility in soil.

Information not available.

12.5. Results of PBT and vPvB assessment.

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

12.6. Other adverse effects.

Information not available.

SECTION 13. Disposal considerations.

13.1. Waste treatment methods.

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information.

14.1. UN number.

Not applicable.

14.2. UN proper shipping name.

Not applicable.

14.3. Transport hazard class(es).

Not applicable.

14.4. Packing group.

Not applicable.

14.5. Environmental hazards.

Not applicable.

14.6. Special precautions for user.

Not applicable.

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code.

Information not relevant



U-BOND 2K ULTRA part B

Revision nr.2 Dated 04/06/2015 Printed on 04/06/2015 Page n. 8 / 10

SECTION 15. Regulatory information.

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture.

Seveso category. None.

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006.

Product.

Point.

Contained substance.

Point. 56 DIPHENYLMETHANE-4,4'-DIISOCYANATE

Reg. no.: 01-2119457014-47-XXXX
Point. 56 DIPHENYLMETHANE-2,4'-DIISOCYANATE

Reg. no.: 01-2119480143-45-XXXX

Substances in Candidate List (Art. 59 REACH).

None

Substances subject to authorisarion (Annex XIV REACH).

None

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls.

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

German regulation on the classification of substances hazardous to water (VwVwS 2005).

WGK 1: Low hazard to waters

15.2. Chemical safety assessment.

No chemical safety assessment has been processed for the mixture and the substances it contains.

SECTION 16. Other information.

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Carcinogenicity, category 2

Acute Tox. 4

Acute toxicity, category 4

STOT RE 2 Specific target organ toxicity - repeated exposure, category 2

Eye Irrit. 2 Eye irritation, category 2 Skin Irrit. 2 Skin irritation, category 2

STOT SE 3 Specific target organ toxicity - single exposure, category 3

Respiratory sensitization, category 1

Skin Sens. 1 Skin sensitization, category 1

H351 Suspected of causing cancer.

H332 Harmful if inhaled.

H373 May cause damage to organs through prolonged or repeated exposure.

H319 Causes serious eye irritation.

H315 Causes skin irritation.
H335 May cause respiratory irritation.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317 May cause an allergic skin reaction.

EUH204 Contains isocyanates. May produce an allergic reaction.

LEGEND

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008



U-BOND 2K ULTRA part B

Revision nr.2 Dated 04/06/2015 Printed on 04/06/2015 Page n. 9 / 10

SECTION 16. Other information. .../>>

- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

- 1. Regulation (EU) 1907/2006 (REACH) of the European Parliament
- 2. Regulation (EU) 1272/2008 (CLP) of the European Parliament
- 3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
- 4. Regulation (EU) 453/2010 of the European Parliament
- 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
- 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
- 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
- 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
- 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
- The Merck Index. 10th Edition
- Handling Chemical Safety
- INRS Fiche Toxicologique (toxicological sheet)
- Patty Industrial Hygiene and Toxicology
- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- ECHA website

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

Changed TLVs in section 8.1 for following countries:

AUS,

Changed TLVs in section 8.1 for following countries:

AUS,

Changed TLVs in section 8.1 for following countries:

AUS.

Changed TLVs in section 8.1 for following countries:

AUS.

Changed TLVs in section 8.1 for following countries:

AUS

Changed TLVs in section 8.1 for following countries:

AUS,

FΝ



N.P.T. S.r.I. U-BOND 2K ULTRA part B

Revision nr.2 Dated 04/06/2015 Printed on 04/06/2015 Page n. 10 / 10

SECTION 16. Other information. .../>>

Changed TLVs in section 8.1 for following countries: AUS,

Changed TLVs in section 8.1 for following countries: AUS.

Changed TLVs in section 8.1 for following countries: AUS

Changed TLVs in section 8.1 for following countries: AUS,

Changes to previous review:
The following sections were modified:
02 / 03 / 08 / 11 / 12 / 15 / 16.
Changed TLVs in section 8.1 for following countries:
AUS.