

N.P.T. S.r.I.

U-Primer 130

ΕN

Safety data sheet

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name

U-Primer 130

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use

One-component adhesion promoter for the automotive industry

1.3. Details of the supplier of the safety data sheet

Namo	
Name	N.F.1. 3.1.1.
Full address	via Guido Rossa 2
District and Country	40053 Valsamoggia - Loc. Crespellano (BO) Italv
	Tel. +39 051 969109
	Fax +39 051 969837
e-mail address of the competent person	
responsible for the Safety Data Sheet	infoSDS@nptsrl.com
1.4. Emergency telephone number	
For urgent inquiries refer to	Laboratories and manufactory plant - Gropello Cairoli (PV)
	+39 0382 815132 (avaiable from Monday to Friday, only in the following office hours:
	8 30-12 30 13 30-17 00)
	0.00 i 2.00, i 0.00 i i i 00/.

SECTION 2. Hazards identification.

2.1. Classification of the substance or mixture.

The product is classified as hazardous pursuant to the provisions set forth in EC Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of EC Regulation 1907/2006 and subsequent amendments.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

2.1.1. Regulation 1272/2008 (CLP) and following amendments and adjustments.

F-Xn

Hazard classification and indication:

Flam. Liq. 2	H225
Eye Irrit. 2	H319
Resp. Sens. 1	H334
Skin Sens. 1	H317
STOT SE 3	H336

2.1.2. 67/548/EEC and 1999/45/EC Directives and following amendments and adjustments.

Danger Symbols:

R phrases: 11-20-36-42/43-66

The full wording of the Risk (R) and hazard (H) phrases is given in section 16 of the sheet.

2.2. Label elements.

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words:

Danger



Revision nr.2 Dated 2/4/2014 Printed on 2/4/2014 Page n. 2 / 9

SECTION 2. Hazards identification. .../>>

n a position comfortable for
·

2.3. Other hazards.

Information not available.

SECTION 3. Composition/information on ingredients.

3.1. Substances.

Information not relevant.

3.2. Mixtures.

Contains:

Identifica	tion.	Conc. %.	Classification 67/548/EEC.	Classification 1272/2008 (CLP).
METHYL	ETHYL KETO	NE		
CAS.	78-93-3	62 - 66	R66, R67, F R11, Xi R36	Flam. Liq. 2 H225, Eye Irrit. 2 H319, STOT SE 3 H336, EUH066
EC.	201-159-0			
INDEX.	606-002-00-3			
ISOPHOR	RONE DIISOCY	ANATE		
CAS.	4098-71-9	1,5 - 2	T R23, Xn R42/43, Xi R36/37/38, N R51/53, Note 2	Acute Tox. 3 H331, Eye Irrit. 2 H319, Skin Irrit. 2 H315,
EC.	223-861-6			STOT SE 3 H335, Resp. Sens. 1 H334, Skin Sens. 1 H317, Aquatic Chronic 2 H411, Note 2
INDEX.	615-008-00-5			· · · · · · · · · · · · · · · · · · ·
DIPHENY	LMETHANE-4	,4'-DIISOCYANA	ATE	
CAS.	101-68-8	0,9 - 1	Carc. Cat. 3 R40, Xn R20, Xn R42/43, Xn R48/20,	Carc. 2 H351, Acute Tox. 4 H332, STOT RE 2 H373, Eye Irrit. 2 H319,
EC.	202-966-0		XI R36/37/38, Note 2 C	Skin Irrit. 2 H315, STOT SE 3 H335, Resp. Sens. 1 H334, Skin Sens. 1 H317, Note 2 C
INDEX.	615-005-00-9			· · · · · · · ·

Note: Upper limit is not included into the range. The full wording of the Risk (R) and hazard (H) phrases is given in section 16 of the sheet.

T+ = Very Toxic(T+), T = Toxic(T), Xn = Harmful(Xn), C = Corrosive(C), Xi = Irritant(Xi), O = Oxidizing(O), E = Explosive(E), F+ = Extremely Flammable(F+), F = Highly Flammable(F), N = Dangerous for the Environment(N)

SECTION 4. First aid measures.

4.1. Description of first aid measures.

EYES: Remove contact lenses, if present Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention immediately. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. If the subject stops breathing, administer artificial respiration. Get medical advice/attention immediately. INGESTION: Get medical advice/attention immediately. Do not induce vomiting. Do not administer anything not explicitly authorised by a doctor.

4.2. Most important symptoms and effects, both acute and delayed.

For symptoms and effects caused by the contained substances, see chap. 11.

4.3. Indication of any immediate medical attention and special treatment needed. Information not available.



SECTION 5. Firefighting measures.

5.1. Extinguishing media.

SUITABLE EXTINGUISHING EQUIPMENT

Extinguishing substances are: carbon dioxide, foam, chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak.

UNSUITABLE EXTINGUISHING EQUIPMENT

Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

5.2. Special hazards arising from the substance or mixture.

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Excess pressure may form in containers exposed to fire at a risk of explosion. Do not breathe combustion products.

5.3. Advice for firefighters. GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures.

6.1. Personal precautions, protective equipment and emergency procedures.

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions.

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up.

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Check incompatibility for container material in section 7. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections.

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage.

7.1. Precautions for safe handling.

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Vapours may catch fire and an explosion may occur; vapour accumulation is therefore to be avoided by leaving windows and doors open and ensuring good cross ventilation. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. When performing transfer operations involving large containers, connect to an earthing system and wear antistatic footwear. Vigorous stirring and flow through the tubes and equipment may cause the formation and accumulation of electrostatic charges. In order to avoid the risk of fires and explosions, never use compressed air when handling. Open containers with caution as they may be pressurised. Do not eat, drink or smoke during use. Avoid leakage of the product into the environment.

7.2. Conditions for safe storage, including any incompatibilities.

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Store in a well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s).

Information not available.



Revision nr.2 Dated 2/4/2014 Printed on 2/4/2014 Page n. 4 / 9

SECTION 8. Exposure controls/personal protection.

8.1. Control parameters.

Regulatory References:	
United Kingdom	EH40/2005 Workplace exposure limits. Containing the list of workplace exposure limits for use with the Control of Substances Hazardous to Health Regulations (as amended).
Éire	Code of Practice Chemical Agent Regulations 2011.
OEL EU	Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC.
TLV-ACGIH	ACGIH 2012
	METHYL ETHYL KETONE

Fhreshold Limit Value.								
Туре	Country	TWA/8h		STEL/15	min			
		mg/m3	ppm	mg/m3	ppm			
WEL	UK	600	200	899	300	SKIN		
OEL	IRL	600	200	900	300	SKIN		
OEL	EU	600	200	900	300			
TLV-ACGIH		590	200	885	300			

ISOPHORONE DIISOCYANATE							
Threshold Limit Value.							
Туре	Country	TWA/8h	TWA/8h		nin		
		mg/m3	ppm	mg/m3	ppm		
TLV-ACGIH			0,005				

DIPHENYLMETHANE-4,4'-DIISOCYANATE

Threshold Limit Va	lue.				
Туре	Country	TWA/8h		STEL/15n	min
		mg/m3	ppm	mg/m3	ppm
OEL	IRL	0,02		0,07	
TLV-ACGIH		0,051	0,005		

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

8.2. Exposure controls.

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Directive 89/686/EEC and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

Consider the appropriateness of providing antistatic clothing in the case of working environments in which there is a risk of explosion.

EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required. Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.



Revision nr.2 Dated 2/4/2014 Printed on 2/4/2014 Page n. 5 / 9

SECTION 9. Physical and chemical properties.

9.1. Information on basic physical and chemical properties.

Appearance	liquid
Colour	black
Odour	solvent
Odour threshold.	Not available.
pH.	Not available.
Melting point / freezing point.	Not available.
Initial boiling point.	80 °C.
Boiling range.	Not available.
Flash point.	-10 °C.
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Lower inflammability limit.	Not available.
Upper inflammability limit.	Not available.
Lower explosive limit.	0,8 % (V/V).
Upper explosive limit.	11,5 % (V/V).
Vapour pressure.	150 hPa
Vapour density	2,5
Relative density.	0,95 Kg/l
Solubility	Not available.
Partition coefficient: n-octanol/water	Not available.
Auto-ignition temperature.	400 °C.
Decomposition temperature.	Not available.
Viscosity	Not available.
Explosive properties	Not available.
Oxidising properties	Not available.
9.2. Other information.	
VOC (Directive 1999/13/EC) :	61,91 % - 588,10 g/litre
VOC (volatile carbon) :	43,20 % - 410,41 g/litre

SECTION 10. Stability and reactivity.

10.1. Reactivity.

There are no particular risks of reaction with other substances in normal conditions of use.

DIPHENYLMETHANE-4,4'-DIISOCYANATE: decomposes at 274°C. With water it develops carbon dioxide and forms an insoluble solid polymer. Consequently any wet material recovered must be stored in open containers. METHYL ETHYL KETONE: reacts with light metals like aluminium, and with strong oxidising agents; attacks various types of plastic. Decomposes under the effect of heat.

10.2. Chemical stability.

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions.

The vapours may also form explosive mixtures with the air.

DIPHENYLMETHANE-4,4'-DIISOCYANATE: can react dangerously with: alcohols, amines, ammonia, sodium hydroxide, acids, water and strong bases and acids.

METHYL ETHYL KETONE: may generate peroxides on contact with air, light or oxidising agents. Risk of explosion on contact with: hydrogen peroxide and sulphuric acid. It may react dangerously with: oxidising agents, trichloromethane, alkalis. Forms explosive mixtures with the air.

10.4. Conditions to avoid.

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition.

METHYL ETHYL KETONE: avoid exposure to sources of heat.

10.5. Incompatible materials.

METHYL ETHYL KETONE: strong oxidising agents, inorganic acids, ammonia, copper and chloroform.

10.6. Hazardous decomposition products.

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

DIPHENYLMETHANE-4,4'-DIISOCYANATE: nitric oxides, carbon oxides, hydrogen cyanide.

ΕN



FN

SECTION 11. Toxicological information.

11.1. Information on toxicological effects.

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

Acute effects: stinging eyes. Symptoms may include: rubescence, edema, pain and lachrymation.

Vapour inhalation may moderately irritate the upper respiratory trait. Contact with skin may cause slight irritation.

Ingestion may cause health problems, including stomach pain and sting, nausea and sickness.

Inhalation of this product causes sensitization, which may then give rise to a series of inflammatory episodes, most of all characterized by obstruction and affecting the respiratory system. Sometimes, sensitization phenomena arise together with evident rhinitis and asthma. Damages to the respiratory system depend on the inhaled quantity, on the product concentration in the working environment and on the exposure time.

Upon contact with skin, this product causes sensitization (dermatitis). Dermatitis derives from skin irritation on the areas which repeatedly come into contact with the sensitizing agent. Cutaneous lesions may include: erythemas, edemas, papules, vesicles, pustules, scurvies, ulcerations and exudative phenomena, whose intensity varies according to illness seriousness and affected areas. Erythemas, edemas and exudative phenomena prevail during the acute phase. Scurfy skin, dryness, ulcerations and skin thickening prevail during the chronic phase. This product contains highly volatile substances, which may cause serious depression of the central nervous system (CNS) and have negative effects, such as drowsiness, dizziness, slow reflexes, narcosis.

DIPHENYLMETHANE-4,4'-DIISOCYANATE: risk of sensitization even at concentrations lower than TLV in case of spray working.

4825 mg/kg Rattus sp.

2,24 mg/l Rattus sp.

> 7000 mg/kg Rattus sp. 0,04 mg/l Rattus sp. (aereosol)

ISOPHORONE DIISOCYANATE LD50 (Oral). LD50 (Dermal). LC50 (Inhalation).

DIPHENYLMETHANE-4,4'-DIISOCYANATE LD50 (Oral). LD50 (Dermal). LC50 (Inhalation). > 2000 mg/kg Rattus sp.> 9400 mg/kg Oryctolagus sp.

METHYL ETHYL KETONE LD50 (Oral). LD50 (Dermal). LC50 (Inhalation).

2737 mg/kg Rattus sp. 6480 mg/kg Oryctolagus sp. 23,5 mg/l/8h Rattus sp.

SECTION 12. Ecological information.

12.1. Toxicity.

DIPHENYLMETHANE-4,4'-DIISOCYANATE LC50 - for Fish. Chronic NOEC for Algae / Aquatic Plants.

> 1000 mg/l/96h Danio rerio 1640 mg/l Desmodesmus subspicatus

12.2. Persistence and degradability. Information not available.

12.3. Bioaccumulative potential. Information not available.

12.4. Mobility in soil.

Information not available.

12.5. Results of PBT and vPvB assessment.

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

12.6. Other adverse effects.



Information not available.

SECTION 13. Disposal considerations.

13.1. Waste treatment methods.

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Avoid littering. Do not contaminate soil, sewers and waterways.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information.

These goods must be transported by vehicles authorized to the carriage of dangerous goods according to the provisions set out in the current edition of the Code of International Carriage of Dangerous Goods by Road (ADR) and in all the applicable national regulations. These goods must be packed in their original packagings or in packagings made of materials resistant to their content and not reacting dangerously with it. People loading and unloading dangerous goods must be trained on all the risks deriving from these substances and on all actions that must be taken in case of emergency situations.

Road and rail transport:

ADR/RID Class:	3 UN: 1139
Packing Group:	II
Label:	3
Nr. Kemler:	33
Limited Quantity.	5 L
Tunnel restriction code.	(D/E)
Proper Shipping Name:	COATING SOLUTION

Carriage by sea (shipping):

IMO Class: Packing Group: Label: EMS: Marine Pollutant. Proper Shipping Name:	3 UN: 1139 II 3 F-E , <u>S-E</u> NO COATING SOLUTION	
Transport by air:		
IATA:	3 UN: 1139	

Packing Group:	II		
Label:	3		
Cargo:			
Packaging instructions:	364	Maximum quantity:	60 L 🛛 💙
Pass.:			
Packaging instructions:	353	Maximum quantity:	5 L
Special Instructions:	A3		
Proper Shipping Name:	COATING S	OLUTION	

SECTION 15. Regulatory information.

15.1.	Safety.	health and	l environmental	regulations	/legislation	specific fo	or the substan	ce or mixture.

Seveso category.	7b						
Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006. Product.							
Point. Contained substance.	3 - 40 ce.						
Point.	56	DIPHENYLMETHANE-4,4'-DIISOCYANATE					
<u>Substances in Candidate List (Art. 59 REACH).</u> None. <u>Substances subject to authorisarion (Annex XIV REACH).</u> None.							

ΕN



Revision nr.2 Dated 2/4/2014 Printed on 2/4/2014 Page n. 8 / 9

SECTION 15. Regulatory information. .../>>

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012: None.

<u>Substances subject to the Rotterdam Convention:</u> None.

Substances subject to the Stockholm Convention: None.

Healthcare controls.

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

Product not intended for uses provided for by Dir. 2004/42/CE.

15.2. Chemical safety assessment.

No chemical safety assessment has been processed for the mixture and the substances it contains.

SECTION 16. Other information.

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Liq. 2	Flammable liquid, category 2
Carc. 2	Carcinogenicity, category 2
Acute Tox. 3	Acute toxicity, category 3
Acute Tox. 4	Acute toxicity, category 4
STOT RE 2	Specific target organ toxicity - repeated exposure, category 2
Eye Irrit. 2	Eye irritation, category 2
Skin Irrit. 2	Skin irritation, category 2
STOT SE 3	Specific target organ toxicity - single exposure, category 3
Resp. Sens. 1	Respiratory sensitization, category 1
Skin Sens. 1	Skin sensitization, category 1
Aquatic Chronic 2	Hazardous to the aquatic environment, chronic toxicity, category 2
H225	Highly flammable liquid and vapour.
H351	Suspected of causing cancer.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H373	May cause damage to organs through prolonged or repeated exposure.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H335	May cause respiratory irritation.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H317	May cause an allergic skin reaction.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.
EUH204	Contains isocyanates. May produce an allergic reaction.

Text of risk (R) phrases mentioned in section 2-3 of the sheet:

R11 R20 R23 R36	HIGHLY FLAMMABLE. HARMFUL BY INHALATION. TOXIC BY INHALATION. IRRITATING TO EYES.
R36/37/38	IRRITATING TO EYES, RESPIRATORY SYSTEM AND SKIN.
Carc. Cat. 3	Carcinogenicity, category 3.
R40	LIMITED EVIDENCE OF A CARCINOGENIC EFFECT.
R42/43	MAY CAUSE SENSITIZATION BY INHALATION AND SKIN CONTACT.
R48/20	HARMFUL: DANGER OF SERIOUS DAMAGE TO HEALTH BY PROLONGED EXPOSURE THROUGH INHALATION.
R51/53	TOXIC TO AQUATIC ORGANISMS, MAY CAUSE LONG-TERM ADVERSE EFFECTS IN THE AQUATIC ENVIRONMENT.
R66 R67	REPEATED EXPOSURE MAY CAUSE SKIN DRYNESS OR CRACKING. VAPOURS MAY CAUSE DROWSINESS AND DIZZINESS.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)

EN



Revision nr.2 Dated 2/4/2014 Printed on 2/4/2014 Page n. 9 / 9

SECTION 16. Other information. ... / >>

- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation.

GENERAL BIBLIOGRAPHY

- 1. Directive 1999/45/EC and following amendments
- 2. Directive 67/548/EEC and following amendments and adjustments
- 3. Regulation (EC) 1907/2006 (REACH) of the European Parliament
- 4. Regulation (EC) 1272/2008 (CLP) of the European Parliament
- 5. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
- 6. Regulation (EC) 453/2010 of the European Parliament
- 7. Regulation (EC) 286/2011 (II Atp. CLP) of the European Parliament
- 8. The Merck Index. 10th Edition
- 9. Handling Chemical Safety
- 10. Niosh Registry of Toxic Effects of Chemical Substances
- 11. INRS Fiche Toxicologique (toxicological sheet)
- 12. Patty Industrial Hygiene and Toxicology
- 13. N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- 14. ECHA website

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses. Provide appointed staff with adequate training on how to use chemical products.

Changes to previous review: The following sections were modified: 01 / 02 / 08 / 11 / 16.