

**ULTRA F5 Super multifunzione spray**

## Safety data sheet

### SECTION 1. Identification of the substance/mixture and of the company/undertaking

**1.1. Product identifier**

Code: C00133-04239  
Product name: ULTRA F5 Super multifunzione spray

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

Intended use "Aerosol" unlocking / waterproof / protective / degreaser made from paraffin oils and solvents.

**1.3. Details of the supplier of the safety data sheet**

Name: PIGAL s.p.a.  
Full address: Via G. Rossa, 2  
District and Country: 40056 Crespellano (BO)  
ITALIA  
Tel. +39 051969068  
Fax +39 051969353

e-mail address of the competent person

responsible for the Safety Data Sheet

health.safety@pigal.it; pigalab@pigal.it

**1.4. Emergency telephone number**

For urgent inquiries refer to

+39 051969068 ore ufficio (8.30-13; 14-17.30) 118 (contattare il centro antiveneni più vicino)

### SECTION 2. Hazards identification.

**2.1. Classification of the substance or mixture.**

The product is classified as hazardous pursuant to the provisions set forth in EC Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of EC Regulation 1907/2006 and subsequent amendments. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

**2.1.1. Regulation 1272/2008 (CLP) and following amendments and adjustments.**

Hazard classification and indication:

Aerosol 1 H222  
H229

**2.1.2. 67/548/EEC and 1999/45/EC Directives and following amendments and adjustments.**

Danger Symbols:

F+

R phrases:

12

The full wording of the Risk (R) and hazard (H) phrases is given in section 16 of the sheet.

**2.2. Label elements.**

**ULTRA F5 Super multifunzione spray**

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words: Danger

Hazard statements:

**H222** Extremely flammable aerosol.  
**H229** Pressurized container: may burst if heated.

Precautionary statements:

**P210** Keep away from heat / sparks / open flames / hot surfaces. No smoking.  
**P211** Do not spray on an open flame or other ignition source.  
**P251** Pressurized container: do not pierce or burn, even after use.  
**P410+P412** Protect from sunlight. Do not expose to temperatures exceeding 50°C / 122°F.

PROFESSIONAL USE.

**2.3. Other hazards.**

Information not available.

**SECTION 3. Composition/information on ingredients.****3.1. Substances.**

Information not relevant.

**3.2. Mixtures.**

Contains:

Identification.	Conc. %.	Classification 67/548/EEC.	Classification 1272/2008 (CLP).
<b>Liquefied petroleum gas</b> CAS. 68476-40-4 EC. 270-681-9 INDEX. 649-199-00-1 Reg. no. 01-211948657-22	45 - 47,5	F+ R12, Note K	Flam. Gas 1 H220, Press. Gas H280, Note K
<b>NAPHTA (PETROL.) HYDROTREATED HEAVY</b> CAS. 64742-48-9 EC. 265-150-3 INDEX. 649-327-00-6 Reg. no. 01-2119486659-16	45 - 47,5	Xn R65, Note P	Asp. Tox. 1 H304, Note P

**ULTRA F5 Super multifunzione spray**

**Distillates (petroleum),hydrotreated light naphthenic ; Base oil - unspecified**

CAS. 64742-53-6

7 - 8

Note L

Asp. Tox. 1 H304, Note L

EC. 265-156-6

INDEX. 649-466-00-2

Reg. no. 01-2119480 375-34

Note: Upper limit is not included into the range.

The full wording of the Risk (R) and hazard (H) phrases is given in section 16 of the sheet.

T+ = Very Toxic(T+), T = Toxic(T), Xn = Harmful(Xn), C = Corrosive(C), Xi = Irritant(Xi), O = Oxidizing(O), E = Explosive(E), F+ = Extremely Flammable(F+), F = Highly Flammable(F), N = Dangerous for the Environment(N)

**SECTION 4. First aid measures.****4.1. Description of first aid measures.**

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention immediately. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. If the subject stops breathing, administer artificial respiration. Get medical advice/attention immediately.

INGESTION: Get medical advice/attention immediately. Do not induce vomiting. Do not administer anything not explicitly authorised by a doctor.

**4.2. Most important symptoms and effects, both acute and delayed.**

For symptoms and effects caused by the contained substances, see chap. 11.

**4.3. Indication of any immediate medical attention and special treatment needed.**

Information not available.

**SECTION 5. Firefighting measures.****5.1. Extinguishing media.**

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

**5.2. Special hazards arising from the substance or mixture.**

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

If overheated, aerosol cans can deform, explode and be propelled considerable distances. Put a protective helmet on before approaching the fire. Do not breathe combustion products.

**5.3. Advice for firefighters.**

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained

**ULTRA F5 Super multifunzione spray**

open circuit positive pressure compressed air breathing apparatus (BS EN 137).

**SECTION 6. Accidental release measures.****6.1. Personal precautions, protective equipment and emergency procedures.**

Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site. Send away individuals who are not suitably equipped. Wear protective gloves / protective clothing / eye protection / face protection.

**6.2. Environmental precautions.**

Do not disperse in the environment.

**6.3. Methods and material for containment and cleaning up.**

Use inert absorbent material to soak up leaked product. Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

**6.4. Reference to other sections.**

Any information on personal protection and disposal is given in sections 8 and 13.

**SECTION 7. Handling and storage.****7.1. Precautions for safe handling.**

Avoid bunching of electrostatic charges. Do not spray on flames or incandescent bodies. Vapours may catch fire and an explosion may occur; vapour accumulation is therefore to be avoided by leaving windows and doors open and ensuring good cross ventilation. Do not eat, drink or smoke during use. Do not breathe spray.

**7.2. Conditions for safe storage, including any incompatibilities.**

Store in a place where adequate ventilation is ensured, away from direct sunlight at a temperature below 50°C, away from any combustion sources.

**7.3. Specific end use(s).**

Information not available.

**SECTION 8. Exposure controls/personal protection.****8.1. Control parameters.**

Regulatory References:

United Kingdom EH40/2005 Workplace exposure limits. Containing the list of workplace exposure limits for use with the Control of Substances Hazardous to Health Regulations (as amended).

Éire Code of Practice Chemical Agent Regulations 2011.

OEL EU Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC.

**ULTRA F5 Super multifunzione spray**

TLV-ACGIH      ACGIH 2012

**Liquefied petroleum gas****Threshold Limit Value.**

Type	Country	TWA/8h		STEL/15min	
		mg/m3	ppm	mg/m3	ppm
TLV-ACGIH			1000		

**NAPHTA (PETROL.) HYDROTREATED HEAVY****Threshold Limit Value.**

Type	Country	TWA/8h		STEL/15min	
		mg/m3	ppm	mg/m3	ppm
TLV-ACGIH		525	100		
MAK		300	50		

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

**8.2. Exposure controls.**

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

**HAND PROTECTION**

None required.

**SKIN PROTECTION**

Wear category I professional long-sleeved overalls and safety footwear (see Directive 89/686/EEC and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

**EYE PROTECTION**

Wear airtight protective goggles (see standard EN 166).

**RESPIRATORY PROTECTION**

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, a mask with a type AX filter combined with a type P filter should be worn (see standard EN 14387).

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

**SECTION 9. Physical and chemical properties.****9.1. Information on basic physical and chemical properties.**

Appearance	liquid (pressurized)
Colour	dark brown
Odour	characteristic of solvent
Odour threshold.	Not available.
pH.	Not available.
Melting point / freezing point.	< -80 °C.

**ULTRA F5 Super multifunzione spray**

Initial boiling point.	Not applicable.
Boiling range.	Not available.
Flash point.	Not applicable.
Evaporation Rate	Not available.
Flammability of solids and gases	flammable gas
Lower inflammability limit.	Not available.
Upper inflammability limit.	Not available.
Lower explosive limit.	1,8 % (V/V).
Upper explosive limit.	9,5 % (V/V).
Vapour pressure.	Not available.
Vapour density	>2 (propellente, Aria =1)
Relative density.	0,640 Kg/l
Solubility	soluble in organic solvents
Partition coefficient: n-octanol/water	Not available.
Auto-ignition temperature.	> 400 °C.
Decomposition temperature.	Not available.
Viscosity	Not available.
Explosive properties	Not available.
Oxidising properties	Not available.

**9.2. Other information.**

VOC (Directive 1999/13/EC) :	93,00 % - 595,20 g/litre.
VOC (volatile carbon) :	0
Can pressure:	3.2 bar after filling at 20°C

**SECTION 10. Stability and reactivity.****10.1. Reactivity.**

There are no particular risks of reaction with other substances in normal conditions of use.

NAPHTA (PETROL.) HYDROTREATED HEAVY - Reacts with strong oxidants causing fire and explosion hazard.

**10.2. Chemical stability.**

The product is stable in normal conditions of use and storage.

**10.3. Possibility of hazardous reactions.**

No hazardous reactions are foreseeable in normal conditions of use and storage.

**10.4. Conditions to avoid.**

Avoid overheating.

**10.5. Incompatible materials.**

Strong reducing or oxidising agents, strong acids or alkalis, hot material.

It may generate flammable gases on contact with elementary metals, nitrides, and strong reducing agents. It may generate toxic gases on contact with oxidising mineral acids, organic peroxides and hydroperoxides.

It may catch fire on contact with oxidising mineral acids, nitrides, peroxides and organic hydroperoxides, strong oxidizing agents.

**10.6. Hazardous decomposition products.**

**ULTRA F5 Super multifunzione spray**

Information not available.

**SECTION 11. Toxicological information.**

According to currently available data, this product has not yet produced health damages. Anyway, it must be handled carefully according to good industrial practices. This product may have slight health effects on sensitive people, by inhalation and/or cutaneous absorption and/or contact with eyes and/or ingestion.

**11.1. Information on toxicological effects.**

**PETROLEUM GAS** - The substance can be absorbed into the body by a loss inalazione.Causa liquid evaporates very quickly displacing the air and causing a serious risk of suffocation when in chiusi.Una Rapid evaporation of the liquid may cause frostbite.

The substance may cause effects on the central nervous system.

**ACUTE HAZARDS / SYMPTOMS**

**INHALATION** Drowsiness. Unconsciousness.

**SKIN ON CONTACT WITH LIQUID: FREEZING.**

**EYE CONTACT WITH LIQUID: FREEZING.**

**NAPHTA (PETROL.) HYDROTREATED HEAVY**

**ROUTES OF EXPOSURE:** The substance can be absorbed into the body by inhalation of its vapor and by ingestion.

**INHALATION RISK:** There can be no indication of the speed with which it reaches aN harmful contamination of the air by evaporation of this substance at 20 ° C.

**EFFECTS OF SHORT-TERM EXPOSURE:** The vapor is slightly irritating to the eyes The substance may have effects on the central nervous system exposure to high concentration of vapors can lead to a state of unconsciousness. If this liquid is swallowed , aspiration into the lungs may result in chemical pneumonitis.

**EFFECTS OF LONG-TERM OR REPEATED EXPOSURE :** The liquid defats the skin.

**ACUTE HAZARDS / SYMPTOMS - INHALATION** Dizziness. Headache . Drowsiness. Nausea . Unconsciousness.

**SKIN** Dry skin .

**EYES** Redness .

Ingestion Cough. Diarrhea. Sore throat. Vomiting. (Further see Inhalation). Symptoms of chemical pneumonitis do not become manifest until a few hours or a few days and they are aggravated by physical effort.

**NOTES** This is a mixture of C9 -C13 naphthenes, iso - and n-paraffins . Neither the concentration of aromatics nor of hexane is greater than 0.1% by volume .

**NAPHTA (PETROL.) HYDROTREATED HEAVY**

LD50 (Oral). 5000 mg/kg Rat

LD50 (Dermal). 5000 mg/kg Rat

LC50 (Inhalation). 5000 mg/l - 4h Rat

**SECTION 12. Ecological information.**

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or sewers or contaminate soil or vegetation.

**12.1. Toxicity.**

**NAPHTA (PETROL.) HYDROTREATED HEAVY** - The substance is toxic to aquatic organisms.

Liquefied petroleum gas

EC50 - for Crustacea.

14,22 mg/l/48h daphnia magna

**NAPHTA (PETROL.) HYDROTREATED HEAVY**

**ULTRA F5 Super multifunzione spray**

LC50 - for Fish.

> 1000 mg/l/96h Oncorhynchus mykiss

EC50 - for Crustacea.

> 1000 mg/l/48h Daphnia magna

EC50 - for Algae / Aquatic Plants.

> 1000 mg/l/72h Pseudokirchneriella subcapitata,

**12.2. Persistence and degradability.**

Information not available.

**12.3. Bioaccumulative potential.**

Liquefied petroleum gas

Partition coefficient: n-octanol/water.

< 2,8 mg/l

**12.4. Mobility in soil.**

Information not available.

**12.5. Results of PBT and vPvB assessment.**

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

**12.6. Other adverse effects.**

Information not available.

**SECTION 13. Disposal considerations.**

The valid EEC waste code are largely source-related; the manufacturer is, therefore, unable to specify waste code for products used in various sectors.  
CER-code (suggested): 16 05 04.

**13.1. Waste treatment methods.**

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Avoid littering. Do not contaminate soil, sewers and waterways.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

**SECTION 14. Transport information.**

These goods must be transported by vehicles authorized to the carriage of dangerous goods according to the provisions set out in the current edition of the Code of International Carriage of Dangerous Goods by Road (ADR) and in all the applicable national regulations. These goods must be packed in their original packagings or in packagings made of materials resistant to their content and not reacting dangerously with it. People loading and unloading dangerous goods must be trained on all the risks deriving from these substances and on all actions that must be taken in case of emergency situations.

**Road and rail transport:**

ADR/RID Class:

2

UN:

1950

**ULTRA F5 Super multifunzione spray**

Packing Group: -  
Label: 2.1  
Nr. Kemler: --  
Limited Quantity: 1 L  
Tunnel restriction code: (D)  
Proper Shipping Name: AEROSOLS

**Carriage by sea (shipping):**

IMO Class: 2.1 UN: 1950

Packing Group: -  
Label: 2.1  
EMS: F-D, S-U  
Marine Pollutant: NO  
Proper Shipping Name: AEROSOLS

**Transport by air:**

IATA: 2 UN: 1950

Packing Group: -  
Label: 2.1  
Cargo:  
Packaging instructions: 203 Maximum quantity: 150 Kg  
Pass.:  
Packaging instructions: 203 Maximum quantity: 75 Kg  
Special Instructions: A145, A167, A802  
Proper Shipping Name: AEROSOLS

**SECTION 15. Regulatory information.****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture.**

Seveso category. 8

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006.

Contained substance.

Point. 28-29 Liquefied petroleum gas Reg. no.: 01-211948657-22

Substances in Candidate List (Art. 59 REACH).

None.

Substances subject to authorisation (Annex XIV REACH).

**ULTRA F5 Super multifunzione spray**

None.

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None.

Substances subject to the Rotterdam Convention:

None.

Substances subject to the Stockholm Convention:

None.

Healthcare controls.

Information not available.

**15.2. Chemical safety assessment.**

No chemical safety assessment has been processed for the mixture and the substances it contains.

**SECTION 16. Other information.**

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

<b>Flam. Gas 1</b>	Flammable gas, category 1
<b>Aerosol 1</b>	Aerosol, category 1
<b>Aerosol 3</b>	Aerosol, category 3
<b>Press. Gas</b>	Pressurised gas
<b>Asp. Tox. 1</b>	Aspiration hazard, category 1
<b>H220</b>	Extremely flammable gas.
<b>H222</b>	Extremely flammable aerosol.
<b>H229</b>	Pressurized container: may burst if heated.
<b>H280</b>	Contains gas under pressure; may burst if heated.
<b>H304</b>	May be fatal if swallowed and enters airways.

Text of risk (R) phrases mentioned in section 2-3 of the sheet:

<b>R12</b>	EXTREMELY FLAMMABLE.
<b>R65</b>	HARMFUL: MAY CAUSE LUNG DAMAGE IF SWALLOWED.

**LEGEND:**

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008

**ULTRA F5 Super multifunzione spray**

- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

**GENERAL BIBLIOGRAPHY**

1. Directive 1999/45/EC and following amendments
2. Directive 67/548/EEC and following amendments and adjustments
3. Regulation (EC) 1907/2006 (REACH) of the European Parliament
4. Regulation (EC) 1272/2008 (CLP) of the European Parliament
5. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
6. Regulation (EC) 453/2010 of the European Parliament
7. Regulation (EC) 286/2011 (II Atp. CLP) of the European Parliament
8. Regulation (EC) 618/2012 (III Atp. CLP) of the European Parliament
9. The Merck Index. - 10th Edition
10. Handling Chemical Safety
11. Niosh - Registry of Toxic Effects of Chemical Substances
12. INRS - Fiche Toxicologique (toxicological sheet)
13. Patty - Industrial Hygiene and Toxicology
14. N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
15. ECHA website

**Note for users:**

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

**Changes to previous review:**

The following sections were modified:

01 / 02 / 03 / 04 / 05 / 06 / 07 / 08 / 09 / 10 / 11 / 12 / 13 / 14 / 15 / 16.