

**DECLARATION OF PERFORMANCE**

According to Annex III of Reg. (EU) n°305/2011

**ACRYLFUOCO 240**

DOP C00154-D-01

EN 15651-1: **F-EXT-INT**

Acrylic sealant for facades, for interior and exterior application

Address of manufacturer

**PIGAL S.r.l**  
**Via G. Rossa, 2 40053 Località Crespellano**  
**VALSAMOGGIA (BO) – ITALY**

Evaluation and verification of the construction product performance systems, according to Annex V:

System 3, System 3 for reaction to fire

The notified body **SKZ TeConA GmbH**, identification number **01213**, performed the determination of the product-type and fire behavior under System 3, in reference to EN 15651, releasing the following:

The performance of the product identified is in conformity with the declared performance (see below). This declaration of performance is issued under the sole responsibility of the manufacturer.

Valsamoggia, 27/01/2017

*Carlo Alberto GOLDONI*  
*Legale Rappresentante - **PIGAL S.r.l.***



**DECLARED PERFORMANCE**EN 15651-1: **F-EXT-INT Class 7,5P**

Conditioning: Method A (ISO 8340)

Substrate: Mortar M2 (without primer)

<b>Essential characteristics</b>	<b>performance</b>	<b>Harmonized specification</b>
Reaction to fire (EN 13501)	Class E	
Release of chemical dangerous to the environment and health	See product safety data sheet	
Water tightness and air tightness		EN 15651-1 & 4: 2012
Resistance to flow (ISO 7390)	≤ 3 mm	
Loss of volume (ISO 10563)	≤ 25 %	
Tensile properties - Elongation after immersion in water (ISO 10591)	≥ 25 %	
Durability	No failure	